



Wiking Miro 4 Wood Burning Stove

Like all the other models in the series, the Wiking Miro 4 is a convection stove which heats up and distributes the air to the room quickly. The Miro 4 has a solid cast iron bottom in the combustion chamber and a robust cast iron door. The Miro 4 has a practical storage space below the combustion chamber, which is opened by pressing lightly on the door.

Wiking Automatic

In a Wiking wood-burning stove, the regulation of air during lighting and re-stocking is managed automatically through the Wiking Automatic device. A heat-sensitive bimetallic spring expands or contracts depending on the temperature in the wood-burning stove.

The Wiking Automatic offers many advantages including:

- Better comfort
- Easier lighting
- Clean and efficient combustion
- Minor impact on the environment

The combustion chamber

All Wiking stoves have a highly-insulated combustion chamber of Vermiculite plates. Vermiculite is a natural material originating from Africa, which has superior insulating capacity combined with a low weight when compared to firebricks from other manufacturers. The Vermiculite plates ensure a temperature increase which is fast enough for the combustion to be clean and efficient.

Design Features

- Automatic Control
- Unique Door Locking System
- Top Or Rear Flue

HETAS

Approved Smoke Control

Exempt

Fuel Type Wood Logs

Nominal Heat Output 4.9 kw

Sarsen Energy Ltd Unit 1 Garlands Trading Estate Cadley Road Collingbourne Ducis
Marlborough Wiltshire SN8 3EB
01264 850742
info@sarsenenergy.co.uk



Maximum Heat Output 8.0 kw

Efficiency Rating Ce13240 78.0 %

Maximum Wood Length 330 mm

Warranty Period 1 Years

Height 1008 mm

Width 468 mm

Depth 356 mm

Height To Centre Of Rear Flue 864 mm

Rear Edge To Centre Top Flue 139 mm

Flue Outlet Diameter Internal 153 mm

Distance Rear From Combustible 150 mm

Distance Side From Combustible 400 mm

Distance Rear Non Combustible 50 mm

Distance Side Non Combustible 50

Plinth Height 70 mm

Weight 87 kg