

Further Woodwarm Boiler options

The Woodwarm 16kw stove is the second largest stove in our range. A grand stove enabling you to burn logs up to 23" long. This stove combines the virtues of all the Woodwarm stoves with the classic clean burn system, generating a clear and clean view of the fire at all times.

Efficiency Rating:-

73.6% on Wood

69.3% on Anthracite

The standard finish for the above stove is metallic black, although the following finishes are also available from the factory:

Rich Brown Metallic, Honey Glow Brown, Blue Metallic and Forest Green.
(Ask your Dealer for a colour chart).

This stove is also available in the following options:

- Wildwood (dedicated wood burner only).
- Straight Sided.
- Brass handles.
- Flat Top (with edges folded down).
- Profiled Top (10mm thick plate top cut with our Laser profiler).
- Curved Canopy.(shown here)

Accessories available are:

- Plinth Stands Incorporating Log Store - 200mm High (Other heights available on request)
- Pedestal Stands - 200mm high
- 50mm Legs
- 100mm Legs
- 125mm Legs
- 150mm Legs
- Vertical rear flue adaptor

Boiler options available are:

- 8,000 Btu Slab Boiler (takes the place of the rear fire board) 1 inch bsp thread 1 inlet 1 outlet.
- 20,000 Btu Slab Boiler (takes the place of the rear fire board, tho larger than the 8kw) 1 inch bsp thread 1 inlet 1 outlet.

25,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.

- 27,000 Btu Slab Boiler (takes the place of the rear fire board) 1 inch bsp thread 1 inlet 1 outlet.
- 35,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 42,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 12-18,000 Btu Roof Boiler (takes the place of the standard flat top and can only be used as an addition to any of the combinations above) 1 inch bsp thread 1 inlet 1 outlet.
- Please see instruction manual for plumbing suggestions.

As with all the Fireview Range this 16kw has a fully riddling grate system and ashpan collection. Riddling can be performed from outside the stove keeping the door shut and the mess inside.

The Woodwarm 20kw stove is the largest stove in our range, with a staggering total boiler capacity of 70,000 btu`s to water and still 3.7kw of heat to the room. This stove's air is controlled via a boiler thermostat. This stove combines the virtues of all the Woodwarm stoves with the classic clean burn system, generating a clear and clean view of the fire at all times.

Efficiency Rating:-

73.6% on Wood

69.3% on Anthracite

The standard finish for the above stove is metallic black, although the following finishes are also available from the factory:

Rich Brown Metallic, Honey Glow Brown, Blue Metallic and Forest Green.

(Ask your Dealer for a colour chart).

This stove is also available in the following options:

- Wildwood (dedicated wood burner only).
- Straight Sided.
- Brass handles.
- Flat Top (shown here with edges folded down).

Sarsen Energy Ltd Unit 1 Garlands Trading Estate Cadley Road Collingbourne Ducis
Marlborough Wiltshire SN8 3EB
01264 850742
info@sarsenenergy.co.uk

- Profiled Top (10mm thick plate top cut with our Laser profiler).
- Curved Canopy.

Accessories available are:

- Plinth Stands Incorporating Log Store - 200mm High (Other heights available on request)

- Pedestal Stands - 200mm high
- 50mm Legs
- 100mm Legs
- 125mm Legs
- 150mm Legs
- Vertical rear flue adaptor

Boiler options available are:

- 8,000 Btu Slab Boiler (takes the place of the rear fire board) 1 inch bsp thread 1 inlet 1 outlet.
- 20,000 Btu Slab Boiler (takes the place of the rear fire board, tho larger than the 8kw) 1 inch bsp thread 1 inlet 1 outlet.
- 25,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 27,000 Btu Slab Boiler (takes the place of the rear fire board) 1 inch bsp thread 1 inlet 1 outlet.
- 35,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 42,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 53,000 Btu Split Saddle Boiler (takes the place of all the fire boards) 1 inch bsp thread 2 inlets 2 outlets.
- 12-18,000 Btu Roof Boiler (takes the place of the standard flat top and can only be used as an addition to any of the combinations above) 1 inch bsp thread 1 inlet 1 outlet.
- Please see instruction manual for plumbing suggestions.

As with all the Fireview Range this 20kw has a fully riddling grate system and ashpan collection. Riddling can be performed from outside the stove keeping the door shut and the mess inside.